

YS01英式挂头式喉箍（British type hose clamp with tube housing）

| 加紧范围<br>Size | 带宽<br>bandwidth | 产品货号<br>ItemNo |               |               | 只/袋     | 只/箱        | 建议安装扭力                 |
|--------------|-----------------|----------------|---------------|---------------|---------|------------|------------------------|
| mm           | mm              | W1             | W2            | W4            | pcs/bag | pcs/carton | suggestedinstalltorque |
| 8-14         | 9.7             | YS01A9814      | YS01B9814     | YS01D9814     | 100     | 2000       | 3.0Nm                  |
| 11-17        | 9.7             | YS01A91117     | YS01B91117    | YS01D91117    | 100     | 2000       | 3.0Nm                  |
| 13-20        | 9.7             | YS01A91320     | YS01B91320    | YS01D91320    | 100     | 2000       | 3.0Nm                  |
| 15-24        | 9.7             | YS01A91524     | YS01B91524    | YS01D91524    | 100     | 2000       | 3.0Nm                  |
| 18-28        | 9.7             | YS01A91828     | YS01B91828    | YS01D91828    | 100     | 2000       | 3.0Nm                  |
| 22-32        | 9.7             | YS01A92232     | YS01B92232    | YS01D92232    | 50      | 1000       | 3.0Nm                  |
| 26-38        | 9.7             | YS01A92638     | YS01B92638    | YS01D92638    | 50      | 500        | 3.0Nm                  |
| 32-44        | 9.7             | YS01A93244     | YS01B93244    | YS01D93244    | 50      | 500        | 3.0Nm                  |
| 38-50        | 9.7             | YS01A93850     | YS01B93850    | YS01D93850    | 50      | 500        | 3.0Nm                  |
| 44-56        | 9.7             | YS01A94456     | YS01B94456    | YS01D94456    | 25      | 500        | 3.0Nm                  |
| 50-65        | 9.7             | YS01A95065     | YS01B95065    | YS01D95065    | 25      | 250        | 3.0Nm                  |
| 58-75        | 9.7             | YS01A95875     | YS01B95875    | YS01D95875    | 25      | 250        | 3.0Nm                  |
| 68-85        | 9.7             | YS01A96885     | YS01B96885    | YS01D96885    | 10      | 250        | 3.0Nm                  |
| 77-95        | 9.7             | YS01A97795     | YS01B97795    | YS01D97795    | 10      | 250        | 3.0Nm                  |
| 15--24       | 11.7            | YS01A121524    | YS01B121524   | YS01D121524   | 50      | 500        | 4.8Nm                  |
| 19--28       | 11.7            | YS01A121928    | YS01B121928   | YS01D121928   | 50      | 500        | 4.8Nm                  |
| 22--32       | 11.7            | YS01A122232    | YS01B122232   | YS01D122232   | 50      | 500        | 4.8Nm                  |
| 26--38       | 11.7            | YS01A122638    | YS01B122638   | YS01D122638   | 50      | 500        | 4.8Nm                  |
| 32--44       | 11.7            | YS01A123244    | YS01B123244   | YS01D123244   | 50      | 500        | 5.2Nm                  |
| 38--50       | 11.7            | YS01A123850    | YS01B123850   | YS01D123850   | 50      | 500        | 5.2Nm                  |
| 44--56       | 11.7            | YS01A124456    | YS01B124456   | YS01D124456   | 25      | 500        | 5.2Nm                  |
| 50--65       | 11.7            | YS01A125065    | YS01B125065   | YS01D125065   | 25      | 500        | 5.2Nm                  |
| 58--75       | 11.7            | YS01A125875    | YS01B125875   | YS01D125875   | 25      | 200        | 5.2Nm                  |
| 68--85       | 11.7            | YS01A126885    | YS01B126885   | YS01D126885   | 25      | 200        | 5.2Nm                  |
| 77--95       | 11.7            | YS01A127795    | YS01B127795   | YS01D127795   | 10      | 200        | 5.2Nm                  |
| 87--112      | 11.7            | YS01A1287112   | YS01B1287112  | YS01D1287112  | 10      | 200        | 5.2Nm                  |
| 104--138     | 11.7            | YS01A12104138  | YS01B12104138 | YS01D12104138 | 10      | 100        | 5.2Nm                  |
| 130--165     | 11.7            | YS01A12130165  | YS01B12130165 | YS01D12130165 | -       | 100        | 5.2Nm                  |
| 150--180     | 11.7            | YS01A12150180  | YS01B12150180 | YS01D12150180 | -       | 100        | 5.2Nm                  |
| 175--205     | 11.7            | YS01A12175205  | YS01B12175205 | YS01D12175205 | -       | 100        | 5.2Nm                  |
| 200--231     | 11.7            | YS01A12200231  | YS01B12200231 | YS01D12200231 | -       | 50         | 5.2Nm                  |
| 226--256     | 11.7            | YS01A12226256  | YS01B12226256 | YS01D12226256 | -       | 50         | 5.2Nm                  |
| 251--282     | 11.7            | YS01A12251282  | YS01B12251282 | YS01D12251282 | -       | 50         | 5.2Nm                  |
| 277--307     | 11.7            | YS01A12277307  | YS01B12277307 | YS01D12277307 | -       | 50         | 5.2Nm                  |

| 材质<br>Material | 钢带<br>Band        | 箍头<br>Housing                       | 螺丝<br>Screw       |
|----------------|-------------------|-------------------------------------|-------------------|
| W1             | Zinc plated steel | Steel with zinc coating or Painting | Zinc plated steel |
| W2             | AISI 430SS        | AISI 304SS                          | Zinc plated steel |
| W4             | AISI 304SS        | AISI 304SS                          | AISI 304SS        |
| W5             | AISI 316SS        | AISI 316SS                          | AISI 316SS        |



根据客人要求，其他规格和材质也能够提供。  
According to the requirement of customers, other sizes and material are also available.  
以上信息仅供参考，不作为技术规范：  
All the information is just for your reference, can't be used as specification

钢带非镂空式涡轮蜗杆喉箍